

# 4CHR3 | 4CHPROR3

## WIFI SMART SWITCH WITH RF CONTROL



#### **FEATURES**

- Remotely control connected lights or devices via APP
- 3 Working modes with self-locking, interlock and inching mode for even remote-control garage door and roller blinds
- Support scheduling a timer to make devices automatically start and stop to work
- Customize smart scenes to make the device connected with the switch to trigger other devices
- Share the control permission of devices to other accounts to control together
- Check real-time ON/OFF status of devices on your mobile phone
- Power on state allows users to set the On/Off/Keep status for the connected device before power failure and ensure it remains the arranged status after power restoration

$\sim$	n	N	т	R١	$\cap$	
	U	IN		$\mathbf{R}$	U	ш

V OI	:e C	ont	rol
V OIL		UIII	.i Ut

**APP Control** 

**RF Control** 





### **SPECIFICATIONS**

SI Edil Ida II day				
Model	4CHR3	4CHPROR3		
Input	100-240V AC 50/60Hz	AC: 100-240V 50/60Hz (DC: 9-23V)		
Output	100-240V AC 50/60Hz			
Max. Load	10A/2200W/Gang 16A/3500W/Total	10A/2200W/Gang 40A/8800W/Total		
WIFI Standard	IEEE802.11 b/g/n 2.4GHz (2400M-2483.5M)			
Gang	4-gang			
Dimensions	145 x 90 x 34 mm			
Weight	228g	241g		
Certification	CE, FCC, RoHS			
Operating Humidity	5%-95%RH, Non-condensing			
Operating Temperature	-10°C - 40°C			
Security Mechanism	WPA/WPA2			
Operating System	Android 4.1 & iOS 9.0	Android 4.1 & iOS 9.0 or Higher		
Antenna	PCB Board with Antenna			

#### **COMPARISON TABLE**

	4CHR3	4CHPROR3
433 MHz Remote Control	-	Yes
Dry Contact	-	Yes
AC Input	Yes	Yes
DC Input	-	Yes
3-Month Operation Records	Yes	Yes
Interlock Mode	APP	APP
Inching Mode	APP	APP

E-mail

Tel no

PC940 Fireproof and Flame-Retardant

Material PC VO

\*All product specifications and product images are subject to change without notice.



CONTACT US Website www.cme.co.za sales@cme.co.za

012 666 9066/8





