

FSP150AHAN1

150 W AC/DC Adapter



Plug Type: Power mini-DIN (4P)

****Meet ErP & PSE**

CB CE ENEC CCC UL IV

Specifications


- Input Voltage Range: 90-264 VAC
- Input Frequency: 47-63 Hz
- Output Voltage: 12 V
- Output Current: 12.5 A
- Output Watts: 150 W
- Efficiency: 87%
- Operating Temperature: 0°C ~ 40°C
- Storage Temperature: -20°C ~ 80°C

Optional Cable

**PN: CB-MD4P4-RS**

16 cm cable for power mini-DIN connector adapter

Dimensions (Unit: mm)




Ordering Information

Part No.	Description
63000-FSP150AHAN1808-RS	12V 150W power adapter with DIN 4-pin+LOCK 90~264 VAC input, ErP, PSE

FSP120AAB

120W AC/DC Adapter



Plug Type: Power mini-DIN (4P)

****Meet ErP & PSE**

CB CE ENEC CCC N UL IV

Specifications


- Input Voltage Range: 90-264 VAC
- Input Frequency: 47-63 Hz
- Output Voltage: 19 V
- Output Current: 6.32 A
- Output Watts: 120 W
- Efficiency: 86%
- Operating Temperature: 0°C ~ 40°C
- Storage Temperature: -40°C ~ 85°C

Optional Cable

**PN: CB-MD4P4-RS**

16 cm cable for power mini-DIN connector adapter

Dimensions (Unit: mm)



Ordering Information

Part No.	Description
63000-FSP120AAB-RS	19 V 120W Power adapter, 90~264 VAC input, ErP, PSE

63040-010096

96W AC/DC Adapter



Plug Type: øin 2.5 mm / øout 5.5 mm

****Meet ErP & PSE**

Specifications


- Input Voltage Range: 90-264 VAC
- Input Frequency: 47-63 Hz
- Output Voltage: 12 V
- Output Current: 8 A
- Output Watts: 96 W
- Efficiency: 87%
- Operating Temperature: 0°C ~ 40°C
- Storage Temperature: -30°C ~ 60°C

Optional Cable

**PN: CB-MD4P4-RS**

16 cm cable for power mini-DIN connector adapter

Dimensions (Unit: mm)



Ordering Information

Part No.	Description
63040-010096-010-RS	12V 96W power adapter with Din 4-pin/lock 90~264 VAC input, ErP, PSE

1

Industrial
Computing
Solutions

2

Video
Capture
Solutions

3

Embedded
Computing
Solutions

4

Automation
Control

5

ORing
Network
Communication

6

Power Supply/
Peripherals

7

Panel
Solutions
Introduction