

CONV-LAN-FIB-MM-SC

MULTI MODE FIBER TRANCEIVER



FEATURES

- Multi-mode Fast Ethernet Fiber Transceiver
- Power Cord and Manual Included
- Power: AC 110V-240V to DC 5V; DC 48V to DC 5V
- Operating standards: IEEE802.3u, 10/100Base-TX and 100Base-FX



SPECIFICATIONS

Fiber Type	Multi-mode
Operating Standards	IEEE802.3u, 10/100Base-TX and 100Base-FX
Connector	
UTP	RJ-45 10/100Mbps
Fiber	SC 100Mbps
Cable	
UTP	Cat. 5 UTP (the max distance up to 100m)
Fiber: Single Mode	50/125, 62.5/125 m (the max distance up to 2km or 5km)
Flow Control	
Full Duplex	Supporting standard IEEE802.3x
Half Duplex	Backpressure
LED	Power, FX FDX, FX Link/Act, TX 100, TX FDX, TX Link/Act.
Power	AC 110V-240V to DC 5V; DC 48V to DC 5V
Ambient Temperature	0 – 70 °C
Humidity	5% - 90%
Dimensions	
Internal Power	30×110×140mm
External Power	26×70×93mm
*All product specifications and product images are subject to change without notice.	