

DH-2U-Serial



Input Condition:

Model No	Voltage	Frequency	Rurrent(unit:A)		Inrush Current		PFC		EMI
			115Vac	230Vac	115Vac	230Vac	115VAC	230Vac	
DH-2U-600P	100-240Vac	47-63Hz	10A	5A	60A	80A	≧ 0.95	≧ 0.90	Class B
DH-2U-800P	100-240Vac	47-63Hz	10A	5A	60A	80A	≧ 0.95	≧ 0.90	Class B

Output Range

Model No	Watt.	Output						
		+5V	+3.3V	12V1	12V2	-5V	-12V	5Vsb
DH-2U-600P	550W	30A	20A	20A	20A	×	0.5A	2.5A
DH-2U-800P	700W	30A	25A	27A	27A	×	0.5A	2.5A
Reguration Load		±5%	±5%	±5%	×	×	±10%	±5%
Ripple And Noise		50mV	50mV	120mV	×	×	120mV	50mV

Specifications:

Efficiency: 80%(230V,Full Load)

Power Good Signal(P.G信号延时): 100-500ms

Hold Time: 16mS(min,70% full load)

Rise Time: 20mS(max,Full Load))

Output Protection: OPP,OVP,OCP,SCP

Remot ON/OFF Control: TTL HIGH/PS-OFF V=0.8V Max;

TTL HIGH/PS-ON V=2.0V Min

Temperature Range: Operating:0 to 50℃;Storage:-40 to 80℃

The Power Supply meet: FCC CLASS B; CISPR22 CLASS B

