

3.2. PDS-700 & PPDS-700-MTCP Programmable Device Servers




Introduction

The PDS-700 series is a family of Programmable Device Servers, also known as "Serial-to-Ethernet gateway", that are designed for linking RS-232/422/485 devices to an Ethernet network. The user-friendly VxComm Driver/Utility allows users to easily turn the built-in COM ports of the PDS-700 series into standard COM ports on a PC. By virtue of its protocol independence, a small-core OS and high flexibility, the PDS-700 series is able to meet the demands of every network-enabled application.

The PDS-700 series includes a powerful and reliable Xserver programming structure that allows you to design your robust Ethernet applications in one day. The built-in, high-performance MiniOS7 boots the PDS-700 up in just one second and gives you fastest responses.

The PPDS-700-MTCP series features true IEEE 802.3af-compliant (classification, Class 1) Power over Ethernet (PoE) using a standard category 5 Ethernet cable to receive power from a PoE switch like the NS-205PSE. The PPDS-700-MTCP also works as a Modbus/TCP to Modbus/RTU gateway that supports most SCADA/HMI communications based on the Modbus/TCP protocol.

The PDS-720(D) and PPDS-720(D)-MTCP is equipped with 1 RS-232 port and 1 RS-485 port. The removable on-board terminal block connector is designed for easy and robust wiring in industrial situations.




Applications

Factory, Building and Home Automation

RS-232/RS-485

Features

- Incorporate Serial Devices in an Ethernet network
- Virtual COM on Windows NT 4.0, 2000/XP/2003 and Vista32
- Powerful Programmable Device Server
- Watchdog Timer suitable for use in harsh environments
- Power Reverse Polarity Protection
- Serial Port +/-4 kV ESD Protection Circuit
- Self-Tuner ASIC Controller on the RS-485 Port
- 5-digit LED Display (for versions with a display)
- RoHS Compliant with no Halogen
- Built-in High Performance MiniOS7 from ICP DAS
- 10/100 Base-TX Ethernet, RJ-45 Port (Auto-negotiating, auto MDI/MDI-X, LED indicator)
- PPDS-720(D)-MTCP supports Modbus/TCP and Modbus/RTU
- PPDS-720(D)-MTCP supports PoE (IEEE 802.3af, Class 1)
- Low power consumption
- Palm-Sized with multiple Serial Ports
- Made from fire retardant materials (UL94-V0 Level)




System Specifications

Models	PDS-720	PDS-720D	PPDS-720-MTCP	PPDS-720D-MTCP
CPU				
CPU	80186, 80 MHz or compatible			
SRAM	512 KB			
Flash Memory				
Flash Memory	Flash ROM: 512 KB; Erase unit is one sector (64 KB); 100,000 erase/write cycles			
EEPROM				
EEPROM	16 KB: Data retention: 40 years; 1,000,000 erase/write cycles			
Built-in Watchdog Timer				
Built-in Watchdog Timer	Yes			
Communication Interface				
Non-isolated	COM1	RS-232 (Tx/D, Rx/D, RTS, CTS, GND)		
	COM2	RS-485 (D2+, D2-, GND)		
Ethernet		10/100 Base-TX, RJ-45 port (Auto-negotiating, auto MDI/MDI-X, LED indicator)		
PoE		- IEEE 802.3af		
COM Port Formats				
Data Bit		7, 8: for COM1 and COM2		
Parity		None, Even, Odd, Mark, Space		
Stop Bit		1: for COM1 and COM2		
Baud Rate		115200 bps max.		
LED Indicators				
5-digit 7 Segment		-	Yes	-
System		Red		
PoE		- Green		
Power				
Protection		Power Reverse Polarity Protection		
Required Supply Voltage		+10 V _{DC} ~ +30 V _{DC} (non-regulated)	PoE or +12 V _{DC} ~ +48 V _{DC} (non-regulated)	
Power Consumption		2.0 W	2.7 W	2.2 W
2.9 W				
Mechanical				
Flammability		Fire Retardant Materials (UL94-V0 Level)		
Dimensions		72 mm x 112 mm x 35 mm (W x H x D)		
Installation		DIN-Rail or Wall mounting		
Environment				
Operating Temperature		-25 °C ~ +75 °C		
Storage Temperature		-40 °C ~ +80 °C		
Humidity		5 ~ 90% RH, non-condensing		


Pin Assignments

Terminal No.	Pin Assignment
E1	Link/Act 10/100M
COM1	01 CTS1 02 RTS1 03 RxD1 04 TxD1 05 INIT*
COM2	06 D2+ 07 D2- 08 (R)+Vs 09 (B)GND




Wiring


2-wire RS-485 Wiring



3-wire RS-232 Wiring



Dimensions (Unit: mm)



Ordering Information

PDS-720 CR	Programmable Device Server with 1 RS-232 port and 1 RS-485 port (RoHS) Includes One CA-0910 Cable
PDS-720D CR	Programmable Device Server with 1 RS-232 port, 1 RS-485 port and an LED Display (RoHS) Includes One CA-0910 Cable
PPDS-720-MTCP CR	Programmable Device Server with PoE, Modbus/TCP, 1 RS-232 port and 1 RS-485 port (RoHS) Includes One CA-0910 Cable
PPDS-720D-MTCP CR	Programmable Device Server with PoE, Modbus/TCP, 1 RS-232 port, 1 RS-485 port and an LED Display (RoHS) Includes One CA-0910 Cable

Accessories

GPSU06U-6	24 V _{DC} /0.25 A, 6 W Power Supply
MDR-20-24	24 V _{DC} /1 A, 24 W Power Supply with DIN-Rail Mounting
DIN-KA52F-48	48 V _{DC} /0.52 A, 25 W Power Supply with Din-Rail Mounting
CA-0903	9-Pin Female D-Sub and RS-232 Connector Cable, 30 cm Cable
CA-0910	9-Pin Female D-Sub and 3-wire RS-232 Cable, 1 m Cable
NS-205 CR	Unmanaged 5-port Industrial Ethernet Switch (RoHS)
NS-205PC CR	Unmanaged Ethernet Switch with 4 PoE Ports and 1 RJ-45 Uplink (RoHS)