


PPC-IN15(SS)-I5-8G-256G-P10
15" Industrial Panel PC



Features

- 15" TFT LED with PCAP Touch
- Intel i5-10210U
- 1x DDR4 2400MHz 8GB. Max up to 32GB
- 2xLAN, 2xRS232/422/485, 8KV Static Electricity & 600W TVS Surge Protection
- Built-in TPM2.0 for Hardware-based Security
- Wide voltage DC 9V~36V, with overcurrent, overvoltage and reverse connection protection
- -20°C ~ 70°C extended operating temperature
- IP65 Compliant Front Panel



Specifications

CPU	Intel i5-10210U
L2 Cache	6MB Intel Smart cache
Chipsets	Intel Bay Trail SOC
Memory	DDR4 2400MHz 8GB, Up to 32GB
Hard Disk	1 x mSATA 256G SSD
Graphics	Intel HD Graphics
Network	Intel® I211-AT GbE LAN
Audio	Realtek ACL662 Audio Controller
TPM	TPM 2.0
Operation System	Windows 7 8 10, Linux, Unix, QNX
I/O	1x HDMI 3x USB 2.0 1x USB 3.0 2x LAN 2 x RS-232/422/485 4G,WIFI & Bluetooth (Optional) 1x Power Switch
Panel Size	15" Multi-Touch Projected Capacitive LED Screen (1024x768)
Aspect Ratio	4:3
Display Brightness	350 cd/m2
Backlight Lifetime	50000 Hr (min.)
Viewing Angle	89 / 89 / 89 / 89 (CR≥10) (L / R / U / D)
Transmittance	>90%
Response Time	<5ms
Surface Hardness	≥7H
Supply Voltage	5.0V DC
Touch Life	≥ 3000W
Material	High-strength Al-alloy (PPC-IN15-I5) Stainless Steel (PPC-IN15SS-I5)
Color	Grey (PPC-IN15-I5) Stainless Steel (PPC-IN15SS-I5)
VESA Mounting	100 x 100mm
Waterproof Rate	IP65
Product Dimensions	361 x 285 x 60 mm
Cut-out Size	347 x 271 mm
Packing Size	460 x 180 x 400 mm
Gross Weight	7.0 Kg
Operating Temperature	-20~70°C
Storage Temperature	-30~80°C(-22~176°F)
Relative Humidity	5%~95%@40°C, non-condensing
Vibration Range	5-500 Hz, 0.026 G2/Hz, 2.16 Grms, X Y Z 1 Hour per axis
External Power Supply	AC 100 - 240V~50/60Hz,1.5A
Working Voltage	DC IN 9V~36V
Power Consumption	≤30W

*All product specifications and product images are subject to change without notice.

www.cme.co.za