

ECHO-J-4125-S4L2

Fanless Mini PC



Features

- Intel Celeron J4125
- 6x USB Ports
- DP & HDMI
- Support Triple Display
- Support PXE Boot/Wake-on-LAN
- Support Windows 10/11 & Linux
- Optional RAM and SSD



APPLICATIONS

Enterprise Office | Education | Home | Hospital | Restaurants



PACKING LIST

1x Power Adapter | 1x Power Cable |
1x Bracket | User Manual | 1x QA Card | Screws

Specifications

CPU	Intel Celeron J4125 2.0GHz-2.7GHz	
Cores/Threads	4 Cores, 4 Threads	
Cache	4MB	
TDP	10W	
Chipset	Gemini Lake	
RAM	1x SO-DIMM DDR4 Slot (Max 16GB)	
Storage	MSATA 16G/32G/64G/128G/256G (Optional)	
Audio Card	HD Audio realtek ALC 662/897	
Graphics	Intel UHD Graphics 600	
Network	10/100/1000Mbps Adaptive, intel I225	
Extendable	WIFI Bluetooth Module (M.2 PCIE)	
Operating System	Windows 10/11 & Linux	
External I/O Ports	4x USB3.0 2x USB2.0 1x DP 2x HDMI 2x RJ45 1x DC	1x MIC-IN 1x LINE-OUT 1x TYPE-C 1x CLS 2-4x RS232 C
	1x COM1-2 Pin 1x COM3-4 Pin 1x CPU-FAN 1x JP1 Pin 1x FP AUDIO Pin	1x JP3 Pin 1x TPM Pin 1x GPIO Pin 1x BAT_CON(Battery) 1x Power Switch
Display Mode		4K Support Triple Display Max Resolution(DP): 4096x2160@60Hz Max Resolution(HDMI): 4096x 2160@30Hz
BIOS	Boot Mode	Power on / PXE / Wake-on-LAN
	Virtualization	VT-D / VT-X
	Hyper-Threading	Not Supported
Working Temperature		-10 - 60°C
Environment Temperature		-10 - 60°C
Operating Humidity		0 ~ 95% (Non-condensing)
Static		Direct Contact: 2K Air Discharge: 6K
Operating Voltage		DC 12V – 3A

x All product specifications and product images are subject to change without notice.