

OTEKsys 17" Ecological POS Monitor



Features



1. Spill and Dust proof design in front bezel, ideally for retail and hospitality environment



2. Sturdy and Robust base



3. Two colors logo printing



4. Screen tilting angle freely up to 90 degree vertically



5. Integrate Elo 5 Wires Resistive touch
6. Optional detachable MSR for stock flexibility



7. Optional choices of 2nd display for advertisement application

Specification

Model	OT17TA	OT17TB
Cabinet Color	Black	
Display Area	337.92 * 270.336 mm	
Optimal Resolution	1280 * 1024	
Brightness	350 cd/m² (typ)	
Contrast Ratio	1000:1 (typ)	
Response Time	5 ms (typ)	
LCD Viewing Angle(L/R/U/D)	85 / 85 / 80 / 80	
Input Video signal connector	D-Sub 15 pins	D-Sub& DVI
Power consumption	30W	
Input Frequency	Horizontal: 31.5-60.2 kHz Vertical : 56.3Hz-75Hz	
Power supply	DC 12V +/- 10%	
Temperature	Operating : 0? ~40? Storage : -10? ~50?	
Humidity	Operating : 20%~80% Storage : 10%~90%	
Weight	5.86kg (Net)	
Physical Dimension	399.2 (W) * 381.5 (H) * 200 (D) mm	
Approvals	CE, FCC, BSMI	
Touch	5W wires Taiwan Touch	
Optional Item		
Cabinet Color	White	
MSR	3 tracks	
2nd display	7" / 8.4" / 10.4" Customer Display	
Customer display	VFD	

Dimensions

