

Performance

- ·Android 12/GMS OS and 8GB RAM+128GB storage
- ·10.1 inch IPS screen, 1920x1200 TFT
- ·10-point capacitive touch

Communication

- \cdot Extension interface (3 choose 1, RJ45, RS232, USB Type-A)
- $\cdot \text{Upgrade}$ BT 5.2, fast and more stable
- ·Optional high performance 2D imager designed to data capture

Features

- ·Front 5.0MP + Rear 13.0MP, autofocus with flashlight
- ·Symmetric speakers. More immersive, more clear.
- $\cdot \text{User-friendly buttons designed for efficient action} \\$

Reliability

- ·Enhanced rugged corners withstand shock and impact
- $\cdot \mathsf{IP65} \ \mathsf{Waterproof} \ \mathsf{and} \ \mathsf{Dustproof}, \ \mathsf{MIL-STD-810H} \ \mathsf{certified}$

Product Six Views





Specification Parameter

Basic parameters	
Dimension	274.9 x 188.7 x 23.1mm
Weight	Device unit 1140g
Device Color	Black
LCD	10.1 inch TFT 16:10, 1920×1200, 700nits
Touch Panel	10 point capacitive touch screen
Camera	Front 5.0MP Rear 13.0MP
1/0	USB 2.0 Type-A x 1, USB Type-C x 1, SIM Card x 2, TF Card (Three in one card holder), 12PIN Pogo Pin x 1, Ф3.5mm standard earphone jack x 1
Extension interface (3 choose 1)	RJ45 (10/100M) x 1 (standard), DB9 (RS232) x 1, USB 2.0 Type-A x 1
Power	USB Type-C interface, supports fast charging PE+2.0, maximum power of 18W, maximum 9V/2A
Performance parameter	
CPU	ARM (OCTA Core)
OS	Android 12/GMS
RAM	8GB
Storage	128GB

Battery	
Capacity	10000mAh/3.8V
Туре	Removable Li-polymer battery
Endurance	9hrs (50% volume sounds, 50% screen brightness, 1080P HD video display by default)
Network connections	
WIFI	802.11 a/b/g/n/ac (2.4G+5.8G)
Bluetooth	BT5.2 Transmission distance: 10m
4G	LTE FDD: B1/B2/B3/B4/B5/B7/B8/B17/B20/B28A/B28B, WCDMA: B1/B2/B5/B8, GSM: B2/B3/B5/B8, LTE-TDD: B38/B39/B40/B41
GNSS	Support, GPS, Glonass, Beidou
Reliability	
Operate Temperature	−20 °C ~ 60 °C
Store Temperature	−30 °C ~ 70 °C
Humidity	95% Non-Condensing
Rugged Feature	IP65 certified, MIL-STD-810H certified
Drop Height	1.22m drop
Data Collection	
2D	Optional
NFC	13.56MHz, Support ISO/IEC 14443A/B/15693/18092/mifare protocols Card reading distance: 4cm

Accessories











Docking Charger

Hand-strap Removable battery

Fast charging adapter

Vehicle Mount

Application Range

Various modules and accessories can be selected to meet customers' application in various industries.



Outdoor Exploration







