

## BASICR4 Wireless Smart Switch



### Specifications

<b>Input</b>	100 – 240V AC 50/60Hz
<b>Output</b>	100 – 240V AC 50/60Hz
<b>Max. Load</b>	2400W @ 240V
<b>Gang</b>	1-gang
<b>Working Temperature</b>	-10°C ~ 40°C
<b>WIFI</b>	IEEE 802.11 b/g/n 2.4GHz
<b>Material</b>	PC V0
<b>Dimensions</b>	88(H) x 39(W) x 24(Thick) mm
<b>Weight</b>	45.8g
<b>Certification</b>	ETL, CE, FCC, RoHS

\*All product specifications and product images are subject to change without notice.

### Features

- ESP32 Chip
- **Magic Switch Mode:** You can still control the light switch through the app even turning off a traditional wall switch. No matter the wall switch or app remote control, you can enjoy the smart world.
- **“eWeLink-Remote” Control:** BASICR4 is a smart switch with the gateway function of “eWeLink-Remote”. You can add “eWeLink-Remote” sub-devices, use S-Mate2 or R5 to pair with BASICR4, and then set the scene, you can reach the two-way control and local control.
- **Group Control:** You can set groups to control multiple devices at the same time for convenience.
- **Safe and Reliable:** Built-in temperature sensor, the real-time maximum temperature of the entire product can be detected and speculated, which prevents the product from deformation, melting, fire, or live devices from exposure in case of over-temperature.
- BASICR4 has obtained CE, FCC, ETL etc certifications.

### Newly Upgrade Chip

Enhance the basic function and increase the performance while keeping a good price.

