

Model No: MKB-F64-TB-DT

MKB-F64-TB-DT is a desktop rugged stainless steel, water-proof, vandal-proof keyboard with 65 customizable, full-travel keys (including 12 function keys) and integrated OPTICAL trackball.

Due to its unique design and build, it is robust, rust-resistant, water & dust-proof and vandalproof, thus widely used in harsh or unattended public facilities like factory workshop, water & gas factory, underground mine, unattended terminals etc.



Items	Specifications
Key Features	<ul style="list-style-type: none">- Desktop style, no mounting is needed, enjoy the convenience of mobility- Small foot-print, saving premium space- 65 keys including 12 function keys F1~F12- Integrated with optical trackball, NO extra mouse is needed- Protruding full travel (2.0mm) keys with chemically-etched graphics, excellent tactile feedback- Designed to operate in harsh environments- Made of stainless steel-high resistance against rust, corrosion and vandalism- Sealed to meet IP65 up to IP68 rating- PS/2 or USB interface for option- Customizable layout upon customer's request
Material	<ul style="list-style-type: none">- Case and Keys: 304 stainless steel- Trackball: stainless steel (diameter: 38mm)
Electrical Data	<ul style="list-style-type: none">- Power supply voltage: DC 5 V \pm 5%- Current rating: 20 mA- Interface: USB or PS2- EMC Emission: EN55022(B)

Items	Specifications
Environmental Characteristics	<ul style="list-style-type: none"> - Operating temperature: -20° C to + 60° C - Storage temperature: - 40° C to + 80° C - Saline mist: 96 hours, IEC 60512-6 - Damp heat test at + 40° C: 21 days, IEC 60512-6 - Dry heat test at + 85° C: 10 days, IEC 60512-6
Mechanical Data	<ul style="list-style-type: none"> - Actuation force: 120±15g - Key travel: 2.0mm - Lifetime (cycles): Min 5, 000, 000 actuations - Sealing protection: IP65/NEMA4X from the front - Vibration resistance: 5 Hz -200 Hz, IEC 60512-4 - Shock resistance: 3 axis 150 m/s² -11 ms, IEC 60512-4
Compatible Operation System	<ul style="list-style-type: none"> - PS2: Win NT4, 98SE, 98ME, 2000, XP - USB: Win 98SE, 98ME, 2000, XP, Mac OS9 / OSX, Win7/8.1/10/11
Reliability	<ul style="list-style-type: none"> -MTBF:>20,000 hours -MTTR:<30 minutes
Certification	-FCC,CE,RoHS
Dimension	- 420.00 x 142.61 x 44.25 mm (L x W x H)
Weight	- 2.00 kgs

